# buschfeld

# all you need

to know


#### structure of tracks

Choose the mounting and the direction of the lighting tracks.

System combinations. 3-dimensional sections. track curves as well as T-, crossand star connectors can be used.

Top view or side view: With a drawing you can help us understand your lighting design

Step by step, together we can find answers to open questions and get a good overview.



#### track colour surface colour

Standard colours: alumatt, black, white , bronze




We produce special colours on request. Here are some examples:



### power feed (48 V)

For the power supply with 48 volts, we offer various different options for the power supply: In a long track or a small separate component.

The specific choice of the feeds is necessary if your planning provides for an operating device that is not installed directly on the track.



# mounting kits

The scope of delivery of the wall tracks includes the mounting, there is only one type of mounting is possible.


For pendant, ceiling or recessed tracks, select a mounting kit according to the installation concept.

e.g. cable suspension, set for ceiling mounting (standard 6 mm or mini 2 mm), flat clip or flush mounting.



#### components

Linear track connectors, corner, T-connectors or stars are just as much a part of the portfolio as ceiling boxes, picture ropes, textile cables and other components.




### control gear Casambi

The Buschfeld control gears provide the basis for the 48 volt power supply of the Sense System luminaires with light control.

Decide at which position the control gear is to be used. As a visible device in the design housing or concealed.

For luminaires with Casambi control, in addition to the wall switches, motion detectors, relays and gateways are also available.



# **luminaires** lighting control

Picture lighting, spotlights, pendant luminaires and uplight modules. The lighting tasks

Just as varied is the selection of our luminaires.

- family of luminaires
- adapter alignment - lighting control

CASAMBI Xicato<sup>®</sup>



fiffy

## light colour beam angle

Select a light colour 3000 K 1800 - 3000 K Dim-to-Warm

beam angle or Fifty spots with 15° beam angle including Soraa Snap System™ give you the flexibility to use extra filter attachments.

This allows the beam angle to be adjusted on site during installation, light colour and honeycomb louvre can be adjusted on site.



#### accessories

The shades are an aesthetic accessory, they cover the heat sink of the light heads.

For all luminaires you can choose a shade.

We also offer front shade: in 30 and 100 mm lengths for







#### Support & Service

Whether you are a private customer or a lighting designer, this overview of the system elements can help you to get started with your lighting concept with buschfeld lighting systems.

Our product portfolio is ve and can be used individually for your lighting design. Here we show you an initial selec-

Get creative, the possibilities are manifold, customised products are possible.

When you need help with planning, write us an email or visit our website.

info@buschfeld.de www.buschfeld.de

follow

@buschfeld\_lighting in P

